

[illegible]

Diagrama de un cruce de caminos con una vía principal de 10,00 metros de ancho y una vía secundaria de 6,00 metros de ancho. La vía principal tiene una acera de 2,00 metros, un estacionamiento en línea de 3,50 metros, una calzada de 3,50 metros y otra acera de 1,00 metro. La vía secundaria tiene una acera de 2,00 metros, un estacionamiento en batería de 4,75 metros y una calzada de 3,50 metros. Se muestran las líneas de tráfico y las zonas de estacionamiento.

[illegible]

The diagram illustrates a road cross-section with the following lane widths and markings:

- Central lane: 3.50m wide, marked with a solid line on the left and a dashed line on the right.
- Inner side lanes: 2.00m wide each, marked with dashed lines on both sides.
- Outer side lanes: 2.00m wide each, marked with solid lines on both sides.
- Total road width: 10.00m.
- Arrows indicate traffic flow: straight ahead in the central lane, and left and right turns in the side lanes.

Technical drawing of a roundabout (Rond-point) showing the layout, dimensions, and traffic flow. The drawing includes a central circular island with a diameter of 30.00. The roundabout is surrounded by a circular path with a radius of 5.00. The drawing also shows the approach roads, the exit roads, and the traffic flow indicated by arrows. The drawing is a top-down view of the roundabout.